



12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P HD NVR



VTD-3332B8-A1































4K Output HD IPC

DDNS

Network

PTZ

Audio

MIC

Mobile

USB

Mouse

E-mail

VTD-3332B8-A1 supports 32 CH 12MP / 8MP / 6MP / 5MP / 4MP / $3MP \, / \, 1080P \, / \, 1280x 1024/960P / \, 720P$ high definition IP input, which adopts the advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

VTD-3332B8-A1 supports 32CH IP input, simultaneous 16CH playback, and 4K high definition display. The product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.









SPECIFICATIONS

| | Model | VTD-3332B8-A1 |
|--------------------------------|---|---|
| System | OS | Embedded Linux |
| Video | IP Video Input | 32 CH IPC input |
| | Incoming /Outgoing Bandwidth | 256Mbps / 256Mbps |
| | IP Video Input Resolution | $12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080 P/1280 \times 1024/960 P/720 P/960 H/D1/CIF$ |
| | Output | HDMI1: 3840×2160@60fps/3840×2160@30fps/ 1920×1080/1280×1024/1024×768 HDMI2: 1920×1080/1280×1024/1024×768 VGA × 1: 1920×1080/1280×1024/1024×768 |
| | Compression | H.265S/ H.265+/ H.265/ H.264 |
| | Multi-screen Display | 1/4/6/8/9/13/16/25/32/36 |
| Audio | Network Input | 32 CH IPC audio input |
| | 2-way Audio | RCA × 1 |
| | Local Output | RCA×1 |
| | Compression | G 711 A U |
| | Record Stream | Dual stream recording |
| Record | Resolution | 12MP@20fps; 8MP/ 6MP/5MP/4MP/3MP/1080P/1280×1024/ 960P/ 720P/960H/D1/CIF@30fps(NTSC)/25fps(PAL) |
| | Simultaneous Playback | Max 16 CH |
| Playback | Search | Time slice / time / event / tag search |
| rayouck | Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| | Function | Play, pause, FF, FB, digital zoom, etc. |
| Decoding Capability | Live View/ Playback | 1CH 12MP/4CH 5MP/9CH 720P/16CH D1 |
| | Mode | Manual, sensor, motion, exception, smart events |
| A.1 | Input | 8 CH local alarm input; supports IPC alarm input |
| Alarm | Output | 4 CH |
| | Triggering | Record, snapshot, buzzer, preset, e-mail, etc. |
| | Channel | 32 CH |
| | Face Picture Database | 32 libraries 5000 Face Pictures |
| | Computing Capability | 180 pictures / minute |
| | Face Picture Search | Search by picture is supported |
| | Database Management | Add, modify, delete and search face pictures |
| | Face Picture Adding | Add face pictures through APP, WEB and external import |
| Face | Face Picture Comparison | Support allow list, block list and stranger match alarm |
| | Track | Track display on a map |
| | Statistic Graph of Face Information | Bar graph |
| | Statistic Mode of Face Information | Statistics by day, week, month, quarter as well as customized time period |
| *** | Human/Vehicle | Yes |
| Video Structure Analysis | Classification | |
| Structure | Classification Fisheye | Supports fisheye dewarping via Web Client and mobile APP |


| Network | Interface | RJ45 10/100/1000 Mbps × 2 |
|------------------|-----------------------------|---|
| | Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, 802.1x, ONVIF, etc. |
| | Client Connection | Max.20 users access |
| Mobile Device | OS | iOS, Andriod |
| Storage | HDD Interface | SATA \times 8, up to 8TB per HDD; e-SATA \times 2 |
| | RAID | RAID0, RAID1, RAID5, RAID6, RAID10 |
| Backup | Local Backup | U disk, USB mobile HDD |
| | Network Backup | Yes |
| | USB | USB2.0×2, USB3.0×1 |
| Port | RS 485 | Yes (full-duplex); connect to PTZ or keyboard |
| | Remote Controller | Yes |
| Others | Power Supply | ATX 250W |
| | Consumption | \leq 30W (without HDD) |
| | Dimensions(mm) | $445 \times 436 \times 90(W \times D \times H)$ |
| | Working Environment | -10 ~50 °C, 10% $^{\sim}$ 90% humidity |
| | Certificate | CE, FCC, UL |
| | Environmental Protection | Directive EU RoHS, REACH and WEEE |


FEATURES

- Supports 32 CH 12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P /1280 × 1024/960P/ 720P/960H/D1/CIFIP input
- H.265S/ H.265+/ H.265/ H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor / smart events
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event, tag and smart search
- Supports face detection and comparison
- Supports multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Supports POS information overlay on live view and playback
- Supports RAID0, RAID1, RAID5, RAID6, RAID10
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-
- user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Supports PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Supports NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



DIMENSIONS





REAR PANEL

